

### US006396431B1

## (12) United States Patent

Swanick et al.

### (10) Patent No.:

US 6,396,431 B1

### (45) **Date of Patent:**

May 28, 2002

# (54) PRECISION MICROWAVE/MILLIMETER WAVE MODULATED SIGNAL SOURCE

- (75) Inventors: **David J. Swanick**, Wakefield, RI (US); **Gautam Misra**, Chelmsford, MA (US);
  - Kichul Cho, North Kingstown, RI (US)
- (73) Assignee: The United States of America as represented by the Secretary of the
  - Navy, Washington, DC (US)
- (\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35
  - U.S.C. 154(b) by 0 days.
- (21) Appl. No.: 09/391,881
- (22) Filed: Sep. 7, 1999
- (51) Int. Cl.<sup>7</sup> ...... H02K 23/00
- (52) **U.S. Cl.** ...... **341/177**; 455/115; 370/205; 324/458; 324/527

### (56) References Cited

#### U.S. PATENT DOCUMENTS

3,921,085	Α	*	11/1975	Keane	329/322
4,078,255	A	*	3/1978	Evans	331/78
4,127,819	Α	*	11/1978	Keane	331/9
4,342,008	Α	*	7/1982	Jewett	331/178

4,425,515 A	*	1/1984	Larson 327/116
4,613,821 A	*	9/1986	Sternberg et al 324/323
5,572,213 A	#	11/1996	Noneman et al 342/13
5,963,581 A	*	10/1999	Fullerton et al 375/131
5,995,534 A	*	11/1999	Fullerton et al 375/146

<sup>\*</sup> cited by examiner

Primary Examiner—Michael Horabik Assistant Examiner—Albert K. Wong (74) Attorney, Agent, or Firm—Michael J. McGowan; Michael F. Oglo; Prithvi C. Lall

### (57) ABSTRACT

The precision microwave/millimeter wave modulated signal source is a relatively low cost, compact, highly accurate and stable signal source covering the 2 to 40 Gigahertz frequency range. The pulse width and amplitude level of the output signal can be changed on every pulse in the signal pulse train. Pulse width range is 5 nanoseconds to 1 millisecond. Pulse repetition intervals can be changed between each pulse set with usable range from 10 nanoseconds to 100 milliseconds. Interval parameters can be adjusted with 1 nanosecond resolutions with stabilities of +/-200 picoseconds. The highly accurate and versatile selection of signal parameters, along with its compact size, makes this design useful as an embedded built in test signal source. This built in signal source can be used for verification of system performance for many electronic warfare systems.

### 21 Claims, 2 Drawing Sheets

